

# Cast iron fireplace

## KRATKI WIKTOR DECO 14

### kW Ø 200

SKU: WIKTOR/DECO EAN: 5901350058411



## Technical data

### General data

Version	<b>Front facing</b>
Nominal power (kW)	<b>14</b>
Heating power range (kW)	<b>6-18</b>
Thermal Efficiency (%)	<b>79.5</b>
Flue gas temperature (oC)	<b>286</b>
Max billet length (cm)	<b>45</b>
Minimum required active area of inlet grilles (cm <sup>2</sup> )	<b>≥700</b>
Minimum required active field of outlet grilles (cm <sup>2</sup> )	<b>≥900</b>
diameter of the flue gas outlet	<b>200</b>
COLOUR	<b>Black</b>
CLOSING	<b>No</b>
Materials	<b>Steel, Cast iron</b>
Door opening	<b>Left</b>

### Energetic efficiency

Energy class	<b>A</b>
EEl	<b>105</b>
Seasonal Energy Efficiency (%)	<b>70</b>
Heat output for space heating (kW)	<b>14</b>
CO emission (at 13% O <sub>2</sub> ) ≤ given in %	<b>0.137</b>
CO emission (mg/m <sup>3</sup> )	<b>1710</b>
Pollen emission (mg/m <sup>3</sup> )	<b>15</b>
NO <sub>x</sub> emission (mg/m <sup>3</sup> )	<b>150</b>
OGC emission (mg/m <sup>3</sup> )	<b>91</b>
Flue gas mass flow (g/s)	<b>11.8</b>

## Certifications / Compliance

Certificates **Ecodesign**

## Additional information

Equipment	<b>Air intake - additional option, Ashpan, Decorative glass</b>
FRONT	<b>Steel front with painted glass</b>
Fuel type	<b>Seasoned deciduous wood (humidity ≤20%)</b>
Number of pieces in a package.	<b>2</b>
EAN	<b>5901350058411</b>

## Physical parameters

Width (cm)	<b>73.8</b>
Height (cm)	<b>64.5</b>
Depth (cm)	<b>38.9</b>
Weight (kg)	<b>112</b>

